

High-quality, full-grain semi-aniline thick leather with embossed grain and additional flame treatment. Developed for the contract sector.

Technical Data

Range of application	Furniture, objects, shoes, leather goods of all kind		
Raw material	South-German and Austrian cattle hides		
Tanning / Production	Mineral tanning		
Dyeing	Dyed in drums with high-quality dyes		
Finishing	non solvent PU-finishing		
Leather type	Semianiline, pre-embossed		
Colors on stock	32 (according to color card)		
Order quantity	starting with 1 hide from our stock program		
Special- / Customer's colors	Minimum order quantity of 40 hides		
Delivery conditions	ex works Großbottwar		
Thickness	1.4 - 1.6 mm		
Average size	5.6 m ²		
Grammage	≈ 850 - 1,050 g/m ²		
Light fastness	DIN EN ISO 105-B02	≥ 6	
Tear strength	DIN EN ISO 3377-1	≥ 20 N/mm	
Permanent folding behaviour	DIN EN ISO 5402-1	30,000 flexes	
Rubbing strength	DIN EN ISO 11640		
	dry	500 cycles	≥ 4 - 5
	wet	250 cycles	≥ 3 - 4
	perspiration	80 cycles	≥ 3 - 4
pH-value	DIN EN ISO 4045	> 3.5	
Adhesion of finish	DIN EN ISO 11644 / IUF 470	≥ 2.5 N/10mm	
Fire behaviour	The article fulfills several fire behaviours. Please contact us for further information.		
Treatment / Care	Wipe once a month with a clean, slightly damp cloth. If necessary, only use special cleaner made by LCK.		
Notes	The PCP-content and AZO-dyes of all our leathers comply with the actually valid provisions concerning the by-law chemical prohibition, clause 15, respectively the utensils regulation of the Federal Republic of Germany.		

Again we authenticate that chromium 6 is unverifiable in our leather.

The limit of 5mg PCP/kg won't be overstepped.